# Argos®<sup>3D</sup> - P100

Time-of-Flight Smart Camera



The Argos<sup>3D</sup> - P100 is a new 3D camera, developed by Bluetechnix, operating on the Timeof-Flight (ToF) principle. The Argos<sup>3D</sup> - P100 is equipped with a PMD PhotonICs® 19k-S3 Timeof-Flight 3D chip.

This smart 3D camera delivers depth information and gray value image data for each pixel simultaneously. Therefore, it's possible to analyze scenes based on 3D data only or in combination with 2D grayscale data.

Using active IR illumination, the sensor is able to capture 3D and 2D information at a resolution of 160x120 pixels with up to  $160^*$  frames per second independently of ambient light. With a range of 3m, a field of view of 90° and a size of only 75 x 57 x 26 mm, this USB camera can be used for next generation sensor systems in various application fields like robotics, gesture recognition, HMI or people counting.



## Application Areas

- Robotics & Industry
- Medical
- » Telematics
- Security & Surveillance
- » R&D» Universities





## Highlights

- » 3D depth sensor PMD ToF technology
- » Real-time capture of distance and grayscale information
- » 160 x 120 pixel
- » Up to 160fps\*
- » USB 2.0
- » GenlCam<sup>™</sup> standard
- » Active IR illumination 850nm
- » Field-of-View 90°



Argos<sup>3D</sup> - P100 distance and greyscale information





Time-of-Flight Smart Camera



## Feature Overview

<b>3D TECHNOLOGY</b>	PMD ToF
PIXEL	160 x 120
FPS	up to 160 <sup>*</sup>
POWER SUPPLY	5V <sub>DC</sub> @ 2.6A
USB 2.0	1 x Device
LED SYNC	1
TEMPERATURE RANGE	Commercial 0 to +70 °C
SUPPORTED STANDARD	GenlCam™ standard
SUPPORTED OS	Windows XP/7 (32/64bit) Linux
TRIPOD MOUNT	1 x 1/4"
DIMENSIONS	B75 x H57 x T27mm W2.95" x H2.44" D1.06"

°160fps @ 100µs integration time and 25°C ambient temperature



#### In the box

- Argos<sup>3D</sup> P100
- USB Cable
- » Tripod
- » Power Adapter
- » Documentation

### NISYS ADAF

Advanced Development and Analysis Framework

ADAF by NISYS consists of an operating system independent middleware and a GUI. The middleware provides the following functionalities:

- » Integration of arbitrary sensor devices (Camera, CAN, GPS...)
- » Data recording and replay featuring a microsecond timestamp resolution
- » Synchronization of different sensors
- Framework for development and integration of processing plugins (C/C++)
- » Coupling of plugins via processing graph

Further information on www.nisys.de



ADAF with Argos<sup>3D</sup> - P100

# Ordering Information

www.bluetechnix.com/goto/argos3d-p100

Order No.	Info
150-2001-1	Argos®³ <sup>D</sup> - P100 Time-of-Flight smart camera

BLUETECHNIX GmbH Waidhausenstraße 3/19 | 1140 Wien, Austria P +43 (1) 9142091 x 0 | F +43 (1) 9142091 x 99 www.bluetechnix.com | office@bluetechnix.com

